

In the Claims:

Please amend the claims as follows:

1-15 (Cancelled)

16. (New) A method for transmitting a digital data stream, in which method data clock information and data frame information are recovered from the digital data stream, the method comprising:

providing a digital data stream having successive data stream units,
each data stream unit including

a data frame,

a data block having data bits, and

a frame synchronization word having frame synchronization bits;

receiving the digital data stream;

detecting successive frame synchronization words of the successive
data stream units;

determining the data clock information from a temporal spacing of the
successive frame synchronization words; and

outputting the data clock information in a manner dependent on a
temporal spacing of successive frame synchronization bits.

17. (New) The method of claim 16, wherein providing a digital data stream comprises defining a frame start of a data frame when a plurality of dummy bits precedes a frame synchronization word, the plurality being at least one greater than the sum of the number of frame synchronization bits in the frame synchronization word and the number of data bits in the data block.

18. (New) The method of claim 16, wherein providing a digital data stream comprises preceding the data bits of the data block by two frame synchronization bits.
19. (New) The method of claim 16, wherein providing a digital data stream comprises encompassing useful data to be transmitted with the data bits of each data block.
20. (New) The method of claim 16, wherein providing a digital data stream comprises providing a 32-bit data block.
21. (New) The method of claim 17, further comprising selecting the dummy bits to be logic ones.
22. (New) The method of claim 16, wherein providing a digital data stream comprises including header data in a first data block of each data frame.
23. (New) The method of claim 22, further comprising including superframe synchronization bits in the header data.
24. (New) The method of claim 23, further comprising including information indicative of the start of an assigned superframe in the superframe synchronization bits, the start being indicated by logic zeroes.
25. (New) A data stream receiver for receiving and processing a digital data stream, the data stream receiver comprising:
 - a data stream reception unit for receiving a digital data stream having at least one data stream unit that includes a frame synchronization word having frame synchronization bits and a data block having data bits;
 - a synchronization bit detection unit for detecting the frame synchronization words of successive data blocks of the digital data stream; and

a data clock determination unit for determining a data clock from a temporal spacing of successive frame synchronization words from the digital data stream.

- 26. (New) The data stream receiver of claim 25, further comprising a frame detection unit for detecting a frame start.
- 27. (New) The data stream receiver of claim 25, further comprising a superframe detection unit for detecting a superframe start.
- 28. (New) A digital data stream transmitted by the method of claim 16.
- 29. (New) An interface module that includes a data stream receiver as recited in claim 25.